

A. INTRODUCTION

Noise pollution in an urban area comes from many sources. Some sources are activities essential to the health, safety, and welfare of a city's inhabitants, such as noise from emergency vehicle sirens, garbage collection operations, and construction and maintenance equipment. Other sources, such as traffic, are essential to the viability of a city as a place to live and do business. Although these and other noise-producing activities are necessary to a city, the noise they produce is undesirable. Urban noise detracts from the quality of the living environment, and there is increasing evidence that excessive noise represents a threat to public health.

The noise analysis presented in this chapter focuses on noise sources (i.e., increased vehicular traffic and stationary noise sources) that would result from the operation of the proposed project, and the acceptability of ambient noise levels in the proposed park. Noise effects during construction of the proposed project are analyzed and discussed in Chapter 20, "Construction."

B. NOISE FUNDAMENTALS

Quantitative information on the effects of airborne noise on people is well-documented. If sufficiently loud, noise may interfere with human activities such as sleep, speech communication, and tasks requiring concentration or coordination. It may also cause annoyance, hearing damage, and other physiological problems. Several noise scales and rating methods are used to quantify the effects of noise on people, taking into consideration such factors as loudness, duration, time of occurrence, and changes in noise level with time. However, it must be noted that all the stated effects of noise on people vary greatly with each individual.

"A"-WEIGHTED SOUND LEVEL (dBA)

Noise is typically measured in units called decibels (dB), which are 10 times the logarithm of the ratio of the sound pressure squared to a standard reference pressure squared. Because loudness is important in the assessment of the effects of noise on people, the dependence of loudness on frequency must be taken into account in the noise scale used in environmental assessments. One of the simplified scales that accounts for the dependence of perceived loudness on frequency is the use of a weighting network, known as "A"-weighting, in the measurement system to simulate the response of the human ear. For most noise assessments, the A-weighted sound pressure level in units of dBA is used in view of its widespread recognition and its close correlation with perception. In the current study, all measured noise levels are reported in A-weighted decibels (dBA). Common noise levels in dBA are shown in Table 19-1.

ABILITY TO PERCEIVE CHANGES IN NOISE LEVELS

The average ability of an individual to perceive changes in noise levels is well-documented (see Table 19-2). Generally, changes in noise levels of less than 3 dBA are barely perceptible to most listeners, whereas changes in noise levels of 10 dBA are normally perceived as doubling (or

halving) of noise loudness. These guidelines permit direct estimation of an individual’s probable perception of changes in noise levels.

NOISE DESCRIPTORS USED IN IMPACT ASSESSMENT

Because the sound pressure level unit of dBA describes a noise level at just one moment, and because very few noises are constant, other ways of describing noise over more extended periods have been developed. One way is to describe the fluctuating noise heard over a specific period as if it had been a steady, unchanging sound. For this condition, a descriptor called the “equivalent sound level,” L_{eq} , can be computed. L_{eq} is the constant sound level that, in a given situation and period (e.g., 1 hour, denoted by $L_{eq(1)}$, or 24 hours, denoted by $L_{eq(24)}$), conveys the same sound energy as the actual time-varying sound. Statistical sound level descriptors, such as L_1 , L_{10} , L_{50} , L_{90} , and L_x , are sometimes used to indicate noise levels that are exceeded 1, 10, 50, 90, and x percent of the time, respectively. Discrete event peak levels are given as L_{01} levels.

**Table 19-1
Common Noise Levels**

Sound Source	(dBA)
Military jet, air raid siren	130
Amplified rock music	110
Jet takeoff at 500 meters	100
Freight train at 30 meters	95
Train horn at 30 meters	90
Heavy truck at 15 meters	80–90
Busy city street, loud shout	80
Busy traffic intersection	70–80
Highway traffic at 15 meters, train	70
Predominantly industrial area	60
Light car traffic at 15 meters, city or commercial areas, or residential areas close to industry	50–60
Background noise in an office	50
Suburban areas with medium-density transportation	40–50
Public library	40
Soft whisper at 5 meters	30
Threshold of hearing	0
Note: A 10 dBA increase in level appears to double the loudness, and a 10 dBA decrease halves the apparent loudness.	
Sources: Cowan, James P. <i>Handbook of Environmental Acoustics</i> , Van Nostrand Reinhold, New York, 1994. Egan, M. David, <i>Architectural Acoustics</i> . McGraw-Hill Book Company, 1988.	

**Table 19-2
Average Ability to Perceive Changes in Noise Levels**

Change (dBA)	Human Perception of Sound
2–3	Barely perceptible
5	Readily noticeable
10	A doubling or halving of the loudness of sound
20	A “dramatic change”
40	Difference between a faintly audible sound and a very loud sound
Source: Bolt, Beranek and Newman, Inc., <i>Fundamentals and Abatement of Highway Traffic Noise</i> , Report No. PB-222-703. Prepared for Federal Highway Administration, June 1973.	

For purposes of the proposed project, the maximum 1-hour equivalent sound level ($L_{eq(1)}$) has been selected as the noise descriptor to be used in this noise impact evaluation. $L_{eq(1)}$ is the noise descriptor recommended for use in the *CEQR Technical Manual* for vehicular traffic and construction noise impact evaluation, and is used to provide an indication of highest expected sound levels. The 1-hour L_{10} is the noise descriptor used in the *CEQR Technical Manual* noise exposure guidelines for City environmental impact review classification.

C. NOISE STANDARDS AND CRITERIA

Noise levels associated with the construction and operation of the proposed project would be subject to the emission source provisions of the New York City Noise Control Code and to noise criteria set for the CEQR process. Other standards and guidelines promulgated by federal agencies do not apply to project noise control, but are useful to review in that they establish measures of impacts. Construction equipment is regulated by the Noise Control Act of 1972.

NEW YORK CITY NOISE CONTROL CODE

The New York City Noise Control Code, amended in December 2005, contains prohibitions regarding unreasonable noise, requirements for noise due to construction activities, and specific noise standards, including plainly audible criteria for specific noise sources. In addition, the amended code specifies that no sound source operating in connection with any commercial or business enterprise may exceed the decibel levels in the designated octave bands shown in Table 19-3 at the specified receiving properties.

**Table 19-3
New York City Noise Codes**

Octave Band Frequency (Hz)	Maximum Sound Pressure Levels (dB) as Measured Within a Receiving Property as Specified Below	
	<i>Residential receiving property for mixed-use building and residential buildings (as measured within any room of the residential portion of the building with windows open, if possible)</i>	<i>Commercial receiving property (as measured within any room containing offices within the building with windows open, if possible)</i>
31.5	70	74
63	61	64
125	53	56
250	46	50
500	40	45
1000	36	41
2000	34	39
4000	33	38
8000	32	37

Source: Section §24-232 of the Administrative Code of the City of New York, as amended December 2005.

NEW YORK CEQR NOISE CRITERIA

The *CEQR Technical Manual* contains noise exposure guidelines for use in City environmental impact review, and required attenuation values to achieve acceptable interior noise levels. These values are shown in Tables 19-4 and 19-5. Noise exposure is classified into four categories: “acceptable,” “marginally acceptable,” “marginally unacceptable,” and “clearly unacceptable.” The *CEQR Technical Manual* criteria are based on maintaining an interior noise level for the worst-case hour L_{10} or less than or equal to 45 A-weighted decibels (dBA).

NEW YORK STATE DEPARTMENT OF TRANSPORTATION ENVIRONMENTAL PROCEDURES MANUAL

The guidelines of the *City Environmental Quality Review (CEQR) Technical Manual* will be used to determine appropriate intersection locations for the proposed noise receptors. In addition to being a destination for new vehicle trips to and from the park, the proposed project would also provide connections to and from the West Shore Expressway, a state highway (Route 440). Although environmental analysis of state roadways under the jurisdiction of the New York State Department of Transportation (NYSDOT) normally follows the procedures contained in the NYSDOT *Environmental Procedures Manual (EPM)*, the *CEQR Technical Manual* procedures and guidance are generally more stringent and are considered more appropriate for this analysis.

Table 19-4
Noise Exposure Guidelines For Use in City Environmental Impact Review¹

Receptor Type	Time Period	Acceptable General External Exposure	Airport ³ Exposure	Marginally Acceptable General External Exposure	Airport ³ Exposure	Marginally Unacceptable General External Exposure	Airport ³ Exposure	Clearly Unacceptable General External Exposure	Airport ³ Exposure		
Outdoor area requiring serenity and quiet ²		L ₁₀ ≤ 55 dBA	L _{dn} ≤ 60 dBA	NA	NA	NA	NA	NA	NA		
Hospital, nursing home		L ₁₀ ≤ 55 dBA		55 < L ₁₀ ≤ 65 dBA	60 < L _{dn} ≤ 65 dBA	65 < L ₁₀ ≤ 80 dBA	70 < L ₁₀ ≤ 80 dBA	L ₁₀ > 80 dBA	L _{dn} ≤ 75 dBA		
Residence, residential hotel, or motel	7 AM to 10 PM	L ₁₀ ≤ 65 dBA		65 < L ₁₀ ≤ 70 dBA		70 < L ₁₀ ≤ 80 dBA					
	10 PM to 7 AM	L ₁₀ ≤ 55 dBA		55 < L ₁₀ ≤ 70 dBA		70 < L ₁₀ ≤ 80 dBA					
School, museum, library, court, house of worship, transient hotel or motel, public meeting room, auditorium, outpatient public health facility		Same as Residential Day (7 AM-11 PM)		Same as Residential Day (7 AM-11 PM)		Same as Residential Day (7 AM-11 PM)				Same as Residential Day (7 AM-11 PM)	Same as Residential Day (7 AM-11 PM)
Commercial or office		Same as Residential Day (7 AM-11 PM)		Same as Residential Day (7 AM-11 PM)		Same as Residential Day (7 AM-11 PM)				Same as Residential Day (7 AM-11 PM)	Same as Residential Day (7 AM-11 PM)
Industrial, public areas only ⁴	Note 4	Note 4	Note 4	Note 4		Note 4				Note 4	

Notes:

(i) In addition, any new activity shall not increase the ambient noise level by 3 dBA or more; (ii) *CEQR Technical Manual* noise criteria for train noise are similar to the above aircraft noise standards: the noise category for train noise is found by taking the L_{dn} value for such train noise to be an L_{dn}^v (L_{dn} contour) value.

Table Notes:

- ¹ Measurements and projections of noise exposures are to be made at appropriate heights above site boundaries as given by American National Standards Institute (ANSI) Standards; all values are for the worst hour in the time period.
- ² Tracts of land where serenity and quiet are extraordinarily important and serve an important public need, and where the preservation of these qualities is essential for the area to serve its intended purpose. Such areas could include amphitheatres, particular parks or portions of parks, or open spaces dedicated or recognized by appropriate local officials for activities requiring special qualities of serenity and quiet. Examples are grounds for ambulatory hospital patients and patients and residents of sanitariums and nursing homes.
- ³ One may use FAA-approved L_{dn} contours supplied by the Port Authority, or the noise contours may be computed from the federally approved INM Computer Model using flight data supplied by the Port Authority of New York and New Jersey.
- ⁴ External Noise Exposure standards for industrial areas of sounds produced by industrial operations other than operating motor vehicles or other transportation facilities are spelled out in the New York City Zoning Resolution, Sections 42-20 and 42-21. The referenced standards apply to M1, M2, and M3 manufacturing districts and to adjoining residence districts (performance standards are octave band standards).

Source: New York City Department of Environmental Protection (adopted policy 1983).

Table 19-5

Required Attenuation Values to Achieve Acceptable Interior Noise Levels

	Marginally Acceptable	Marginally Unacceptable		Clearly Unacceptable		
Noise level with proposed action	$65 < L_{10} \leq 70$	$70 < L_{10} \leq 75$	$75 < L_{10} \leq 80$	$80 < L_{10} \leq 85$	$85 < L_{10} \leq 90$	$90 < L_{10} \leq 95$
Attenuation ¹	25 dB(A)	30dB(A)	35 dB(A)	40 dB(A)	45 dB(A)	50 dB(A)
Note:	¹ The above composite window-wall attenuation values are for residential dwellings. Commercial office spaces and meeting rooms would be 5 dB(A) less in each category. All the above categories require a closed window situation and hence an alternate means of ventilation.					
Source:	New York City Department of Environmental Protection (DEP)					

D. IMPACT DEFINITION

As recommended in the *CEQR Technical Manual*, this study uses the following criteria to define a significant adverse noise impact:

- An increase of 5 dBA, or more, in Build $L_{eq(1)}$ noise levels at sensitive receptors (including residences, play areas, parks, schools, libraries, and houses of worship) over those calculated for the No Build condition, if the No Build levels are less than 60 dBA $L_{eq(1)}$ and the analysis period is not a nighttime period.
- An increase of 4 dBA, or more, in Build $L_{eq(1)}$ noise levels at sensitive receptors over those calculated for the No Build condition, if the No Build levels are 61 dBA $L_{eq(1)}$ and the analysis period is not a nighttime period.
- An increase of 3 dBA, or more, in Build $L_{eq(1)}$ noise levels at sensitive receptors over those calculated for the No Build condition, if the No Build levels are greater than 62 dBA $L_{eq(1)}$ and the analysis period is not a nighttime period.
- An increase of 3 dBA, or more, in Build $L_{eq(1)}$ noise levels at sensitive receptors over those calculated for the No Build condition, if the analysis period is a nighttime period (defined by the *CEQR Technical Manual* criteria as being between 10 PM and 7 AM).

E. NOISE PREDICTION METHODOLOGY

INTRODUCTION

The noise impact assessment predicted separately the effects of noise from increased traffic and noise from stationary noise sources in the proposed park. Total noise levels with the proposed project (Build values) were obtained by adding noise due to project-generated traffic and stationary noise sources to noise levels without the proposed project (No Build values). The methodologies used to determine noise effects from these two types of noise are discussed below. Impacts were determined based upon the combined effects of both of these noise sources.

MOBILE NOISE SOURCES

At all of the receptor sites in the study area, the dominant operational noise sources are vehicular traffic on adjacent and nearby streets and roadways. Noise from other sources, such as local or nearby industrial or institutional uses, are limited and do not contribute significantly to local ambient noise levels. To screen area roadways for the potential for a significant project impact, a proportional modeling technique was used to determine approximate increases in noise levels.

To calculate noise from traffic on adjacent and nearby streets and roadways, the Federal Highway Administration [FHWA] *Traffic Noise Model* (TNM, version 2.5) was used. The noise analysis examined three weekday conditions: AM, midday, and PM time periods, and two Saturday conditions: midday and PM time periods. The selected time periods are when the proposed project would have maximum traffic generation and/or the maximum potential for significant adverse noise impacts based on the traffic studies presented in Chapter 16, "Traffic and Parking." The proportional modeling and TNM procedures used for analysis are described below.

PROPORTIONAL MODELING

Proportional modeling was used to determine locations with the potential for having significant noise impacts. Proportional modeling is one of the techniques recommended in the New York City *CEQR Technical Manual* for mobile source analysis.

Using this technique, the prediction of future noise levels, where traffic is the dominant noise source, is based on a calculation using measured existing noise levels and predicted changes in traffic volumes to determine No Build and Build levels. Using this methodology, vehicular traffic volumes were converted into Passenger Car Equivalent (PCE) values, for which one medium-duty truck (having a gross weight between 9,900 and 26,400 pounds) is assumed to generate the noise equivalent of 13 cars; one heavy-duty truck (having a gross weight of more than 26,400 pounds) is assumed to generate the noise equivalent of 47 cars; and one bus (vehicles designed to carry more than nine passengers) is assumed to generate the noise equivalent of 18 cars. Future noise levels are calculated using the following equation:

$$F\ NL - E\ NL = 10 * \log_{10} (F\ PCE / E\ PCE)$$

where:

- F NL = Future Noise Level
- E NL = Existing Noise Level
- F PCE = Future PCEs
- E PCE = Existing PCEs

With this methodology, assuming traffic is the dominant noise source at a particular location if the existing traffic volume on a street is 100 PCE and if the future traffic volume were increased by 50 PCE to a total of 150 PCE, the noise level would increase by 1.8 dBA. Similarly, if the future traffic were increased by 100 PCE, or doubled to a total of 200 PCE, the noise level would increase by 3.0 dBA.

TNM MODEL

The TNM is a computerized model developed for the FHWA that calculates the noise contribution of each roadway segment to a given noise receptor. The noise from each vehicle type is determined as a function of the reference energy-mean emission level, corrected for vehicle volume, speed, roadway grade, roadway segment length, and source-receptor distance. Further considerations included in modeling the propagation path include identifying the shielding provided by rows of buildings, analyzing the effects of different ground types, identifying source and receptor elevations, and analyzing the effects of any intervening noise barriers.

STATIONARY NOISE SOURCES

There would be various non-mobile noise sources in the proposed park which are potential noise generators. These stationary noise sources include sitting areas, picnic areas, outdoor

classrooms, sport fields, parking lots, outdoor amphitheater, etc. After evaluating the magnitude of noise generated by activities within these areas, noise from the outdoor amphitheater was determined as the stationary noise source producing the highest noise level. In addition to the proposed outdoor amphitheater, a proposed parking lot and a proposed softball field would be located near a vehicle entrance on Melvin Avenue, which would have the potential for causing a significant increase in noise levels at nearby residences on Melvin Avenue. Consequently, noise sources for the outdoor amphitheater, the parking lot, and the softball field were selected for the project noise impact assessment purposes. Noise from other activities would be limited and would not contribute significantly to total ambient noise levels.

The emission noise levels for amphitheater were determined by measured data on a similar amphitheater. Based on measured results from Chastain Park Amphitheater (6,000-seat)¹, average $L_{eq(1)}$ noise levels were 85 dBA at 300 feet away from the amphitheater stage. The emission noise levels for softball field were determined by measured data at a series of New York City high school playgrounds for the New York City School Construction Authority (SCA)², and the measured hourly $L_{eq(1)}$ noise level were 68.2 dBA at the playground boundary. It is noted that using these measured noise levels for this noise impact analysis would be conservative. Noise levels with stationary noise sources at receptor sites were calculated based on the measured noise levels using the following formula:

$$L_{eq1} = L_{eq2} - 20 * \text{LOG} (d_1/d_2) - A_{\text{screen}}$$

where:

- L_{eq1} is the noise level at the receptor location;
- L_{eq2} is the measured noise level;
- d_1 is the distance from the source to the receptor;
- d_2 is the distance at which the measured level is known; and
- A_{screen} is the attenuation due to screening.

Noise assessment was performed for the parking lot using the methodology contained in the Federal Transit Administration (FTA) guidance manual³. At 50 feet from the center of the parking lot noise levels were calculated using the following formula:

$$L_{eq(1)} = \text{SEL}_{\text{ref}} + C_N - 35.6$$

Where:

$$C_N = 10 \log (N_A/2000 + N_B/24) \quad \text{for parking \& ride lot}$$

N_A = Number of automobiles per hour,

N_B = Number of buses per hour (N/A)

$\text{SEL}_{\text{ref}} = 101$ for park & ride lot

¹ Another “New” Metric for Outdoor Amphitheater Criteria, Noise-Con 2005, Minneapolis, Minnesota.

² SCA Playground Noise Study, AKRF, Inc., October 23, 1992.

³ Transit Noise and Vibration Impact Assessment, Federal Transit Administration, May 2006.

For this assessment a maximum of 40 autos during the peak hour was assumed. The closest residences from the parking lot would be approximately 150 feet away. Noise levels with the parking lot at noise receptors were calculated using the same formula previously described for the amphitheater noise calculations.

ANALYSIS PROCEDURE

To determine potential noise impacts from project-generated traffic and stationary noise sources, the following procedure was used in performing the noise analysis:

- Determine sensitive receptors within the adjacent study area where the maximum project noise levels would be likely to occur;
- Perform field noise measurements to determine the existing ambient noise levels at the selected receptors;
- Calculate Build noise levels using the methods previously described; and
- Determine total Build noise levels by cumulating noise due to project-generated traffic and stationary noise sources.

F. EXISTING CONDITIONS

SITE DESCRIPTION

The project site (described in detail in Chapter 1, “Project Description”) is all City-owned land (the majority of which is managed by DSNY and DPR) and consists of landfill and open space or parkland/natural areas. The project site fronts the Arthur Kill waterfront to the west and Richmond Avenue to the east. The project site is bisected by the West Shore Expressway. To the north is the William T. Davis Wildlife Refuge. The southern boundary is generally defined by Arthur Kill Road. The project study area consists primarily of open space (City parks and wildlife preserves), and commercial, residential, and industrial uses.

SELECTION OF NOISE RECEPTOR LOCATIONS

Twelve receptor sites in the study area were selected for project impact assessment purposes due to the project-generated traffic and the stationary noise sources, and one additional receptor site (on the dead end of Melvin Avenue) adjacent to the proposed softball field was selected for analyses due to noise from the softball field. Table 19-6 lists the locations of each noise receptor site and their associated existing surrounding land uses. Figure 19-1 shows the receptor site locations and existing land uses. The twelve receptor sites (sites 1-12) used for project-generated traffic and stationary noise sources include representative noise-sensitive locations, principally locations with residential, open space, and institutional land uses, and locations where maximum project impacts would be expected. The additional receptor site, (receptor A) is located at the closest residences adjacent to the proposed softball field, where the project-generated traffic would be limited. At all other locations, particularly locations outside the study area, either project-generated traffic or stationary sources would be less and/or would constitute a small portion to total noise levels, and consequently would not have the potential for causing a significant increase in noise levels.

Table 19-6
Noise Receptor Locations

Receptor	Location	Associated Land Use
1	West Shore Expressway Southbound Service Road at Muldoon Avenue	Fresh Kills Project Area Open Space
2	Arden Avenue between Forest Green and Bunnell Street	Residential/Open Space
3	Arthur Kill Road East of Muldoon Avenue, between Muldoon Avenue and Shopping Center	Residential/Open Space
4	Forest Hill Road between Independence and Richmond Avenues	Open Space
5	Forest Hill Road at Stone Lane	Residential/Open Space
6	Richmond Hill Road between Merry Mount Street and Racal Court	Residential
7	Victory Boulevard between Melvin and Wild Avenues	Residential/School
8	West Shore Expressway Southbound Service Road, South of Victory Boulevard	Residential
9	Arthur Kill Road between Arden Avenue and Carlyle Green	Residential
10	Arthur Kill Road between Cortelyou and Ridgewood Avenues	Residential/Open Space
11	Travis Avenue between Freedom and Mulberry Avenues	Residential/Open Space
12	Victory Boulevard between Travis and Shenandoah Avenues	Residential/Open Space
A*	Dead end of Melvin Avenue adjacent to the proposed park	Residential/Open Space

Note: * Receptor A was selected for assessing noise from the proposed softball field and parking lot.

NOISE MONITORING

At each receptor location, 20-minute noise measurements were made for five time periods to determine existing noise levels. For weekday conditions, noise measurements were taken on October 23 and 31, 2007; on November 27, 2007; on February 27 and 28, 2008; and on March 4 and 5, 2008. For weekend conditions, noise measurements were taken on November 3 and 17, 2007; and on March 1 and 15, 2008.

EQUIPMENT USED DURING NOISE MONITORING

Measurements were performed using Brüel & Kjær Noise Level Meters Type 2260, Brüel & Kjær Sound Level Calibrators Type 4231, and Brüel & Kjær ½-inch microphones Type 4189. The Brüel & Kjær meters are Type 1 noise meters. The instruments were mounted on a tripod at a height of 5 feet above the ground. The meters were calibrated before and after readings using Brüel & Kjær Type 4231 sound level calibrators with the appropriate adaptors. The data were digitally recorded by the sound meters and displayed at the end of the measurement period in units of dBA. Measured quantities included L_{eq} , L_1 , L_{10} , L_{50} , and L_{90} . Windscreens were used during all sound measurements except for calibration. All measurement procedures conformed to the requirements of ANSI Standard S1.13-2005.

RESULTS OF BASELINE MEASUREMENTS

Table 19-7 summarizes the results of the baseline measurements for the Weekday AM, midday, and PM and the Saturday midday and PM analysis hours. In general, noise levels are moderate to relatively high and reflect the level of vehicular activity on the adjacent streets.

In terms of CEQR noise exposure guidelines, during the hour with the highest measured noise levels, based on the measured L_{10} values, existing noise levels at receptors from 1 through 12 are in the “marginally unacceptable” category, and existing noise levels at receptor site A are in the

“acceptable” category.

NOISE MODEL VALIDATION

Although TNM has been shown to be quite accurate predictor of noise levels for most situations, the model was validated for use at twelve receptor sites by comparing measured and modeled predicted noise levels. Using the inputs for the traffic volumes, speeds, roadway alignments, ground reflections, and existing buildings, the TNM model was run to predict the five period traffic noise levels for the existing condition. A difference of 3 dBA or less between the modeled noise levels and measured noise levels indicates that the TNM model can be used with confidence. Based upon the TNM predicted results, all of the modeled noise levels are within 3 dBA of the measured values.

G. THE FUTURE WITHOUT THE PROPOSED PROJECT—2016 AND 2036

The future conditions without the proposed project were analyzed for two analysis years—2016 and 2036. Noise impacts were assessed based on increased traffic.

2016 NO BUILD ANALYSIS

Using the methodology previously described, future noise levels without the proposed action were calculated for all receptors for the 2016 analysis year. These No Build values are shown in Table 19-8.

In 2016, the increase in $L_{eq(1)}$ noise levels would be less than 1.5 dBA at receptor sites from 1 through 12. Changes of these magnitudes would be barely perceptible and insignificant, and they would be below the CEQR threshold for a significant adverse impact. In terms of CEQR Noise Exposure Guidelines, noise levels at receptors from 1 through 12 would remain in the “marginally unacceptable” category.

At receptor site A (i.e., the closest residence adjacent to the proposed parking lot and the softball field), the maximum increase in $L_{eq(1)}$ noise levels would be 5.1 dBA. The major contributor for these increases in noise levels would be noise from No Build traffic increases. Changes of this magnitude would be noticeable, and they would exceed the CEQR threshold for a significant adverse impact. In terms of CEQR Noise Exposure Guidelines, noise levels at receptor site A would remain in the “acceptable” category.

2036 NO BUILD ANALYSIS

Using the methodology previously described, future noise levels without the proposed action were calculated for all receptors for the 2036 analysis year. These No Build values are shown in Table 19-9.

In 2036, the increase in $L_{eq(1)}$ noise levels would be less than 2.2 dBA at receptor sites from 1 through 12. Changes of these magnitudes would be barely perceptible and insignificant, and they would be below the CEQR threshold for a significant adverse impact. In terms of CEQR Noise Exposure Guidelines, noise levels at receptors from 1 through 12 would remain in the “marginally unacceptable” category.

Table 19-7
Measured Existing Noise Levels (in dBA)

Receptor	Location		Time	L _{eq(t)}	L ₁	L ₁₀	L ₅₀	L ₉₀
1	West Shore Expressway Southbound Service Road at Muldoon Avenue	Weekday	AM	71.2	80.5	74.5	67.7	63.5
			MD	72.4	79.0	75.5	70.9	66.2
			PM	71.9	77.6	75.1	70.8	65.4
		Saturday	MD	71.1	77.9	75.2	68.2	64.3
			PM	72.3	78.6	75.8	70.7	64.5
2	Arden Avenue between Forest Green and Bunnell Street	Weekday	AM	73.6	83.1	77.1	70.6	59.4
			MD	72.6	82.0	75.8	70.2	59.9
			PM	72.2	79.8	76.1	69.5	58.7
		Saturday	MD	72.8	80.3	76.4	70.3	58.6
			PM	72.8	79.8	76.5	71.3	60.3
3	Arthur Kill Road East of Muldoon Avenue, between Muldoon Avenue and Shopping Center	Weekday	AM	72.6	82.5	76.0	68.3	57.8
			MD	71.1	80.2	74.7	68.5	59.8
			PM	70.5	76.8	73.8	68.9	59.7
		Saturday	MD	70.3	77.4	73.4	68.8	59.8
			PM	69.7	76.9	72.8	68.3	58.7
4	Forest Hill Road between Independence and Richmond Avenues	Weekday	AM	71.7	79.3	75.1	70.0	59.5
			MD	71.3	79.7	74.7	69.1	58.1
			PM	71.7	80.5	75.1	69.0	58.2
		Saturday	MD	70.1	77.8	73.9	67.9	60.3
			PM	69.2	75.9	72.3	68.0	59.2
5	Forest Hill Road at Stone Lane	Weekday	AM	73.8	81.2	77.7	71.8	59.5
			MD	74.1	80.2	77.6	72.9	63.1
			PM	73.6	80.1	77.1	72.4	61.6
		Saturday	MD	73.7	79.2	76.9	72.9	64.2
			PM	72.3	78.6	75.9	71.2	58.2
6	Richmond Hill Road between Merry Mount Street and Racal Court	Weekday	AM	69.7	80.3	73.5	62.8	54.0
			MD	69.9	79.7	73.3	65.4	57.6
			PM	71.7	83.2	73.7	63.5	54.0
		Saturday	MD	67.8	76.9	71.4	64.7	58.5
			PM	66.2	77.4	68.9	62.3	55.7
7	Victory Boulevard between Melvin and Wild Avenues	Weekday	AM	66.4	75.9	70.1	62.8	57.9
			MD	63.4	73.5	65.9	59.5	55.1
			PM	66.7	76.0	69.6	63.9	57.2
		Saturday	MD	70.3	80.9	73.2	64.0	56.4
			PM	69.0	78.3	72.1	64.2	55.8
8	West Shore Expressway Southbound Service Road, South of Victory Boulevard	Weekday	AM	73.5	85.4	76.5	67.5	63.5
			MD	70.5	79.6	73.0	67.0	63.1
			PM	67.0	76.4	69.8	63.3	59.8
		Saturday	MD	69.1	76.9	72.0	66.7	63.9
			PM	67.5	75.6	70.3	65.4	62.4
9	Arthur Kill Road between Arden Avenue and Carlyle Green	Weekday	AM	69.5	79.2	72.4	66.3	62.1
			MD	70.1	78.7	72.1	64.5	59.5
			PM	67.6	76.3	70.9	65.0	58.6
		Saturday	MD	68.1	77.4	70.8	65.5	59.4
			PM	68.8	77.3	72.5	66.3	57.1
10	Arthur Kill Road between Cortelyou and Ridgewood Avenues	Weekday	AM	73.5	82.4	75.9	71.8	66.1
			MD	72.4	81.3	75.1	70.8	62.7
			PM	63.8	70.8	66.1	62.9	59.2
		Saturday	MD	68.8	76.4	70.6	68.0	61.2
			PM	68.2	75.6	70.4	67.4	60.4
11	Travis Avenue between Freedom and Mulberry Avenues	Weekday	AM	74.6	82.1	77.2	71.6	59.5
			MD	72.8	81.4	76.2	70.4	54.8
			PM	71.7	78.3	75.1	70.1	55.1
		Saturday	MD	70.4	76.0	73.9	69.5	56.9
			PM	70.7	77.2	74.3	69.3	57.0
12	Victory Boulevard between Travis and Shenandoah Avenues	Weekday	AM	70.7	81.1	73.3	67.8	62.1
			MD	70.9	81.9	72.8	66.9	60.8
			PM	71.4	82.5	72.3	67.2	61.9
		Saturday	MD	64.2	69.8	67.1	63.2	58.7
			PM	65.0	71.3	67.7	64.1	58.4
A*	The dead end at Melvin Avenue adjacent to the proposed park	Weekday	AM	54.6	66.0	55.8	51.3	49.7
			MD	51.7	56.5	53.3	50.9	49.4
			PM	52.7	60.1	52.9	50.7	49.4
		Saturday	MD	53.1	58.0	54.9	52.5	51.2
			PM	54.1	61.3	56.0	52.8	50.6

Notes: Field measurements were performed by AKRF, Inc. on October 23 and 31, 2007; on November 3, 17, 27, 2007; on February 27 and 28, 2008; and on March 1, 4, 5 and 15, 2008.
* Receptor A was selected for assessing noise from the proposed softball field and the parking lot.

At receptor site A (i.e., the closest residence adjacent to the proposed parking lot and softball field), the maximum increase in $L_{eq(1)}$ noise levels would be 5.6 dBA. The major contributor for these increases in noise levels would be noise from the No Build traffic increases. Changes of this magnitude would be noticeable, and they would exceed the CEQR threshold for a significant adverse impact. In terms of CEQR Noise Exposure Guidelines, noise levels at receptor site A would remain in the “acceptable” category.

H. THE FUTURE WITH THE PROPOSED PROJECT—2016 AND 2036

The future conditions with the proposed project were analyzed for two analysis years—2016 and 2036. Noise impacts were assessed based on increased traffic and stationary noise sources.

2016 BUILD ANALYSIS

Using the methodology previously described, future noise levels with the proposed action were calculated for the 2016 analysis year. These Build values are shown in Table 19-10.

In 2016, comparing Build with No Build values, the increase in $L_{eq(1)}$ noise levels would be less than 1.0 dBA at receptor sites from 1 through 12. At receptor sites 3, 6, 7, 9, 10, 11, and 12 a decrease in noise levels was predicted to occur for Build conditions due to a decrease of 2016 traffic volume at Arthur Kill Road, Richmond Hill Road, Victory Boulevard, and Travis Avenue. The Build traffic would be expected to decrease at these locations due to the reverse travel pattern caused by the new park roads (see Chapter 16: Traffic and Parking). At those locations where the proposed project would result in an increase in noise levels, the changes would not be perceptible, would be insignificant, and they would be below the CEQR threshold for a significant adverse impact. In terms of CEQR Noise Exposure Guidelines, noise levels at receptors from 1 through 12 would remain in the “marginally unacceptable” category.

At receptor A (i.e., the closest residence adjacent to the proposed softball field) the maximum increase in $L_{eq(1)}$ noise levels would be 3.9 dBA. Changes of this magnitude would be perceptible, but they would be below the CEQR threshold for a significant adverse impact. In terms of CEQR Noise Exposure Guidelines, noise levels at receptor A would remain in the “acceptable” category.

2036 BUILD ANALYSIS

Using the methodology previously described, future noise levels with the proposed action were calculated for the 2036 analysis year. These Build values are shown in Table 19-11.

In 2036, comparing Build with No Build values, the increase in $L_{eq(1)}$ noise levels would be less than 1.0 dBA at receptor sites from 1 through 12. At receptors 3, 7, 9, 10, 11, and 12 a decrease in noise levels was predicted to occur for Build conditions due to a decrease of 2036 traffic volume at Arthur Kill Road, Victory Boulevard, and Travis Avenue. The Build traffic would be expected to decrease at these locations due to the reverse travel pattern caused by the new park roads (see Chapter 16: Traffic and Parking). At those locations where the proposed project would result in an increase in noise levels, the changes would not be perceptible, would be insignificant, and they would be below the CEQR threshold for a significant adverse impact. In terms of CEQR Noise Exposure Guidelines, noise levels at receptors from 1 through 12 would remain in the “marginally unacceptable” category.

**Table 19-8
2016 Future Noise Levels Without the Proposed Action (in dBA)**

Receptor	Location		Time	Existing L _{eq(1)}	No Build L _{eq(1)}	L _{eq(1)} Change	No Build L ₁₀₍₁₎
1	West Shore Expressway Southbound Service Road at Muldoon Avenue	Weekday	AM	71.2	71.9	0.7	75.2
			MD	72.4	73.1	0.7	76.2
			PM	71.9	72.6	0.7	75.8
		Saturday	MD	71.1	71.9	0.8	76.0
			PM	72.3	73.0	0.7	76.5
			AM	73.6	74.4	0.8	77.9
2	Arden Avenue between Forest Green and Bunnell Street	Weekday	MD	72.6	73.4	0.8	76.6
			PM	72.2	73.2	1.0	77.1
			MD	72.8	73.6	0.8	77.2
		Saturday	PM	72.8	73.7	0.9	77.4
			AM	72.6	73.3	0.7	76.7
			MD	71.1	71.8	0.7	75.4
3	Arthur Kill Road East of Muldoon Avenue, between Muldoon Avenue and Shopping Center	Weekday	PM	70.5	71.6	1.1	74.9
			MD	70.3	71.2	0.9	74.3
			PM	69.7	70.7	1.0	73.8
		Saturday	AM	71.7	72.6	0.9	76.0
			MD	71.3	72.3	1.0	75.7
			PM	71.7	72.7	1.0	76.1
4	Forest Hill Road between Independence and Richmond Avenues	Weekday	MD	70.1	71.0	0.9	74.8
			PM	69.2	70.1	0.9	73.2
			AM	73.8	74.8	1.0	78.7
		Saturday	MD	74.1	75.1	1.0	78.6
			PM	73.6	74.6	1.0	78.1
			MD	73.7	74.6	0.9	77.8
5	Forest Hill Road at Stone Lane	Weekday	PM	72.3	73.2	0.9	76.8
			AM	69.7	70.5	0.8	74.3
			MD	69.9	70.7	0.8	74.1
		Saturday	PM	71.7	72.4	0.7	74.4
			MD	67.8	68.6	0.8	72.2
			PM	66.2	66.9	0.7	69.6
6	Richmond Hill Road between Merry Mount Street and Racial Court	Weekday	AM	66.4	67.3	0.9	71.0
			MD	63.4	64.7	1.3	67.2
			PM	66.7	67.9	1.2	70.8
		Saturday	MD	70.3	71.7	1.4	74.6
			PM	69.0	70.4	1.4	73.5
			AM	73.5	74.4	0.9	77.4
7	West Shore Expressway Southbound Service Road, South of Victory Boulevard	Weekday	MD	70.5	71.3	0.8	73.8
			PM	67.0	67.8	0.8	70.6
			MD	69.1	70.0	0.9	72.9
		Saturday	PM	67.5	68.4	0.9	71.2
			AM	69.5	70.3	0.8	73.2
			MD	70.1	70.9	0.8	72.9
8	Arthur Kill Road between Arden Avenue and Carlyle Green	Weekday	PM	67.6	68.3	0.7	71.6
			MD	68.1	68.8	0.7	71.5
			PM	68.8	69.5	0.7	73.2
		Saturday	AM	73.5	74.2	0.7	76.6
			MD	72.4	73.2	0.8	75.9
			PM	63.8	64.5	0.7	66.8
9	Arthur Kill Road between Cortelyou and Ridgewood Avenues	Weekday	MD	68.8	69.6	0.8	71.4
			PM	68.2	69.1	0.9	71.3
			AM	74.6	75.5	0.9	78.1
		Saturday	MD	72.8	73.4	0.6	76.8
			PM	71.7	72.6	0.9	76.0
			MD	70.4	71.2	0.8	74.7
10	Travis Avenue between Freedom and Mulberry Avenues	Weekday	PM	70.7	71.6	0.9	74.2
			MD	70.9	71.8	0.9	73.7
			PM	71.4	72.3	0.9	73.2
		Saturday	MD	64.2	65.1	0.9	68.0
			PM	65.0	66.0	1.0	68.7
			AM	54.6	56.0	1.4	57.2
A*	The dead end at Melvin Avenue adjacent to the proposed park	Weekday	MD	51.7	55.5	3.8	57.1
			PM	52.7	55.7	3.0	55.9
			MD	53.1	57.8	4.7	59.6
		Saturday	PM	54.1	59.2	5.1	61.1

Note: * Receptor A was selected for assessing noise from the proposed softball field.

Table 19-9
2036 Future Noise Levels Without the Proposed Action (in dBA)

Receptor	Location		Time	Existing L _{eq(1)}	No Build L _{eq(1)}	L _{eq(1)} Change	No Build L ₁₀₍₁₎
1	West Shore Expressway Southbound Service Road at Muldoon Avenue	Weekday	AM	71.2	72.7	1.5	76.0
			MD	72.4	74.0	1.6	77.1
			PM	71.9	73.5	1.6	76.7
		Saturday	MD	71.1	72.7	1.6	76.8
			PM	72.3	73.9	1.6	77.4
			AM	73.6	75.2	1.6	78.7
2	Arden Avenue between Forest Green and Bunnell Street	Weekday	MD	72.6	74.2	1.6	77.4
			PM	72.2	73.9	1.7	77.8
			MD	72.8	74.3	1.5	77.9
		Saturday	PM	72.8	74.4	1.6	78.1
			AM	72.6	74.1	1.5	77.5
			MD	71.1	72.7	1.6	76.3
3	Arthur Kill Road East of Muldoon Avenue, between Muldoon Avenue and Shopping Center	Weekday	PM	70.5	72.3	1.8	75.6
			MD	70.3	72.0	1.7	75.1
			PM	69.7	71.3	1.6	74.4
		Saturday	AM	71.7	73.4	1.7	76.8
			MD	71.3	73.1	1.8	76.5
			PM	71.7	73.4	1.7	76.8
4	Forest Hill Road between Independence and Richmond Avenues	Weekday	MD	70.1	71.8	1.7	75.6
			PM	69.2	71.0	1.8	74.1
			AM	73.8	75.5	1.7	79.4
		Saturday	MD	74.1	75.9	1.8	79.4
			PM	73.6	75.4	1.8	78.9
			MD	73.7	75.4	1.7	78.6
5	Forest Hill Road at Stone Lane	Weekday	PM	72.3	74.1	1.8	77.7
			AM	69.7	71.3	1.6	75.1
			MD	69.9	71.4	1.5	74.8
		Saturday	PM	71.7	73.2	1.5	75.2
			MD	67.8	69.4	1.6	73.0
			PM	66.2	67.7	1.5	70.4
6	Richmond Hill Road between Merry Mount Street and Racal Court	Weekday	AM	66.4	68.1	1.7	71.8
			MD	63.4	65.4	2.0	67.9
			PM	66.7	68.6	1.9	71.5
		Saturday	MD	70.3	72.4	2.1	75.3
			PM	69.0	71.0	2.0	74.1
			AM	73.5	75.2	1.7	78.2
7	West Shore Expressway Southbound Service Road, South of Victory Boulevard	Weekday	MD	70.5	72.1	1.6	74.6
			PM	67.0	68.6	1.6	71.4
			MD	69.1	70.8	1.7	73.7
		Saturday	PM	67.5	69.2	1.7	72.0
			AM	69.5	71.1	1.6	74.0
			MD	70.1	71.6	1.5	73.6
8	Arthur Kill Road between Arden Avenue and Carlyle Green	Weekday	PM	67.6	69.1	1.5	72.4
			MD	68.1	69.6	1.5	72.3
			PM	68.8	70.3	1.5	74.0
		Saturday	AM	73.5	75.0	1.5	77.4
			MD	72.4	73.9	1.5	76.6
			PM	63.8	65.3	1.5	67.6
9	Arthur Kill Road between Cortelyou and Ridgewood Avenues	Weekday	MD	68.8	70.4	1.6	72.2
			PM	68.2	69.8	1.6	72.0
			AM	74.6	76.3	1.7	78.9
		Saturday	MD	72.8	74.1	1.3	77.5
			PM	71.7	73.4	1.7	76.8
			MD	70.4	72.0	1.6	75.5
10	Travis Avenue between Freedom and Mulberry Avenues	Weekday	PM	70.7	72.3	1.6	75.9
			AM	70.7	72.4	1.7	75.0
			MD	70.9	72.6	1.7	74.5
		Saturday	PM	71.4	73.1	1.7	74.0
			MD	64.2	65.8	1.6	68.7
			PM	65.0	66.8	1.8	69.5
11	Victory Boulevard between Travis and Shenandoah Avenues	Weekday	AM	54.6	56.7	2.1	57.9
			MD	51.7	55.8	4.1	57.4
			PM	52.7	56.3	3.6	56.5
		Saturday	MD	53.1	58.3	5.2	60.1
			PM	54.1	59.7	5.6	61.6
			AM	54.6	56.7	2.1	57.9
A*	The dead end at Melvin Avenue adjacent to the proposed park	Weekday	MD	51.7	55.8	4.1	57.4
			PM	52.7	56.3	3.6	56.5
			MD	53.1	58.3	5.2	60.1
		Saturday	PM	54.1	59.7	5.6	61.6
			AM	54.6	56.7	2.1	57.9
			MD	51.7	55.8	4.1	57.4

Note: * Receptor A was selected for assessing noise from the proposed softball field.

At receptor A (i.e., the closest residence adjacent to the proposed parking lot and softball field) the maximum increase in $L_{eq(1)}$ noise levels would be 4.6 dBA. The major contributor for these increases in noise levels would be noise from the project-generated traffic. Changes of these magnitudes would be noticeable, but they would not exceed the CEQR threshold for a significant adverse impact. In terms of CEQR Noise Exposure Guidelines, noise levels at receptor A would change from the “acceptable” category to the “marginally acceptable” category.

ACCEPTABILITY OF AMBIENT NOISE LEVELS IN THE PROPOSED PARK

Noise levels within Fresh Kills Park would be above the 55 dBA $L_{10(1)}$. This exceeds the noise level for outdoor areas requiring serenity and quiet contained in the *CEQR Technical Manual* noise exposure guidelines (see Table 19-5). Maximum $L_{10(1)}$ noise levels would be the high 80s dBA at locations near the outdoor amphitheater (when events are taking place in the amphitheatre), maximum $L_{10(1)}$ noise levels would be the high 70s dBA at locations near the West Shore Expressway, and average $L_{10(1)}$ noise levels would be the mid 60s dBA at the center area of proposed park. These predicted noise levels would result from the noise generated by traffic on the nearby West Shore Expressway and new park roadways, as well as activities in the new park. There are no practical and feasible mitigation measures that could be implemented to reduce noise levels to below the 55 dBA $L_{10(1)}$ guideline. However, the noise levels in the new park would be comparable to noise levels in portions of other parks that are also located adjacent to trafficked roadways, including South Shore Golf Course Park, Arden Heights Woods Park, LaTourette Park, and Willowbrook Park. Although the 55 dBA $L_{10(1)}$ guideline is a worthwhile goal for outdoor areas requiring serenity and quiet, this relatively low noise level is typically not achieved in parks and open space areas in New York City. Consequently, noise levels in the Fresh Kills Park, while exceeding the 55 dBA $L_{10(1)}$ CEQR guideline value, would not result in a significant adverse noise impact.

CONCLUSIONS

The proposed project would not result in significant adverse noise impacts from increased traffic or stationary noise sources.

Although noise levels within Fresh Kills Park would be above the *CEQR Technical Manual* noise exposure guideline of 55 dBA $L_{10(1)}$ for outdoor areas requiring serenity and quiet, they would be comparable to noise levels in several other New York City parks, including South Shore Golf Course Park, Arden Heights Woods Park, LaTourette Park, and Willowbrook Park, and would not result in a significant adverse noise impact.

Table 19-10
2016 Future Noise Levels With the Proposed Action (in dBA)

Receptor	Location		Time	No Build L _{eq(1)}	Build L _{eq(1)}	L _{eq(1)} Change	Build L ₁₀₍₁₎
1	West Shore Expressway Southbound Service Road at Muldoon Avenue	Weekday	AM	71.9	72.2	0.3	75.5
			MD	73.1	73.6	0.5	76.7
			PM	72.6	73.0	0.4	76.2
		Saturday	MD	71.9	72.1	0.2	76.2
			PM	73.0	73.3	0.3	76.8
			AM	74.4	74.4	0.0	77.9
2	Arden Avenue between Forest Green and Bunnell Street	Weekday	MD	73.4	73.4	0.0	76.6
			PM	73.2	73.2	0.0	77.1
			MD	73.6	73.7	0.1	77.3
		Saturday	PM	73.7	73.7	0.0	77.4
			AM	73.3	72.8	-0.5	76.2
			MD	71.8	71.5	-0.3	75.1
3	Arthur Kill Road East of Muldoon Avenue, between Muldoon Avenue and Shopping Center	Weekday	PM	71.6	71.1	-0.5	74.4
			MD	71.2	70.8	-0.4	73.9
			PM	70.7	70.2	-0.5	73.3
		Saturday	AM	72.6	72.9	0.3	76.3
			MD	72.3	72.8	0.5	76.2
			PM	72.7	73.0	0.3	76.4
4	Forest Hill Road between Independence and Richmond Avenues	Weekday	MD	71.0	71.3	0.3	75.1
			PM	70.1	70.5	0.4	73.6
			AM	74.8	75.0	0.2	78.9
		Saturday	MD	75.1	75.6	0.5	79.1
			PM	74.6	75.0	0.4	78.5
			MD	74.6	74.9	0.3	78.1
5	Forest Hill Road at Stone Lane	Weekday	PM	73.2	73.6	0.4	77.2
			AM	70.5	70.4	-0.1	74.2
			MD	70.7	70.6	-0.1	74.0
		Saturday	PM	72.4	72.4	0.0	74.4
			MD	68.6	68.6	0.0	72.2
			PM	66.9	66.9	0.0	69.6
6	Richmond Hill Road between Merry Mount Street and Racal Court	Weekday	AM	67.3	66.7	-0.6	70.4
			MD	64.7	64.0	-0.7	66.5
			PM	67.9	67.4	-0.5	70.3
		Saturday	MD	71.7	71.2	-0.5	74.1
			PM	70.4	70.0	-0.4	73.1
			AM	74.4	74.8	0.4	77.8
7	West Shore Expressway Southbound Service Road, South of Victory Boulevard	Weekday	MD	71.3	71.9	0.6	74.4
			PM	67.8	68.0	0.2	70.8
			MD	70.0	70.3	0.3	73.2
		Saturday	PM	68.4	68.8	0.4	71.6
			AM	70.3	67.6	-2.7	70.5
			MD	70.9	68.3	-2.6	70.3
8	Arthur Kill Road between Arden Avenue and Carlyle Green	Weekday	PM	68.3	65.7	-2.6	69.0
			MD	68.8	65.9	-2.9	68.6
			PM	69.5	66.5	-3.0	70.2
		Saturday	AM	74.2	74.2	0.0	76.6
			MD	73.2	73.2	0.0	75.9
			PM	64.5	64.5	0.0	66.8
9	Arthur Kill Road between Cortelyou and Ridgewood Avenues	Weekday	MD	69.6	69.3	-0.3	71.1
			PM	69.1	68.7	-0.4	70.9
			AM	75.5	75.1	-0.4	77.7
		Saturday	MD	73.4	72.9	-0.5	76.3
			PM	72.6	72.4	-0.2	75.8
			MD	71.2	70.9	-0.3	74.4
10	Travis Avenue between Freedom and Mulberry Avenues	Weekday	PM	71.6	71.2	-0.4	74.8
			AM	71.6	71.3	-0.3	73.9
			MD	71.8	71.3	-0.5	73.2
		Saturday	PM	72.3	72.1	-0.2	73.0
			MD	65.1	64.8	-0.3	67.7
			PM	66.0	65.8	-0.2	68.5
11	Victory Boulevard between Travis and Shenandoah Avenues	Weekday	AM	56.0	59.0	3.0	60.2
			MD	55.5	58.2	2.7	59.8
			PM	55.7	58.3	2.6	58.5
		Saturday	MD	57.8	61.4	3.6	63.2
			PM	59.2	63.1	3.9	65.0
			AM	56.0	59.0	3.0	60.2
A*	The dead end at Melvin Avenue adjacent to the proposed park	Weekday	MD	55.5	58.2	2.7	59.8
			PM	55.7	58.3	2.6	58.5
			MD	57.8	61.4	3.6	63.2
		Saturday	PM	59.2	63.1	3.9	65.0
			AM	56.0	59.0	3.0	60.2
			MD	55.5	58.2	2.7	59.8


Note: * Receptor A was selected for assessing noise from the proposed softball field.

**Table 19-11
2036 Future Noise Levels With the Proposed Action (in dBA)**

Receptor	Location		Time	No Build L _{eq(1)}	Build L _{eq(1)}	L _{eq(1)} Change	Build L ₁₀₍₁₎
1	West Shore Expressway Southbound Service Road at Muldoon Avenue	Weekday	AM	72.7	73.2	0.5	76.5
			MD	74.0	74.7	0.7	77.8
			PM	73.5	74.1	0.6	77.3
		Saturday	MD	72.7	73.4	0.7	77.5
			PM	73.9	74.5	0.6	78.0
			AM	75.2	75.2	0.0	78.7
2	Arden Avenue between Forest Green and Bunnell Street	Weekday	MD	74.2	74.2	0.0	77.4
			PM	73.9	74.0	0.1	77.9
			MD	74.3	74.4	0.1	78.0
		Saturday	PM	74.4	74.6	0.2	78.3
			AM	74.1	73.6	-0.5	77.0
			MD	72.7	72.2	-0.5	75.8
3	Arthur Kill Road East of Muldoon Avenue, between Muldoon Avenue and Shopping Center	Weekday	PM	72.3	71.9	-0.4	75.2
			MD	72.0	71.8	-0.2	74.9
			PM	71.3	71.1	-0.2	74.2
		Saturday	AM	73.4	73.6	0.2	77.0
			MD	73.1	73.6	0.5	77.0
			PM	73.4	73.5	0.1	76.9
4	Forest Hill Road between Independence and Richmond Avenues	Weekday	MD	71.8	72.1	0.3	75.9
			PM	71.0	71.3	0.3	74.4
			AM	75.5	75.8	0.3	79.7
		Saturday	MD	75.9	76.4	0.5	79.9
			PM	75.4	75.5	0.1	79.0
			MD	75.4	75.7	0.3	78.9
5	Forest Hill Road at Stone Lane	Weekday	PM	74.1	74.4	0.3	78.0
			AM	71.3	71.8	0.5	75.6
			MD	71.4	71.9	0.5	75.3
		Saturday	PM	73.2	73.7	0.5	75.7
			MD	69.4	69.9	0.5	73.5
			PM	67.7	68.1	0.4	70.8
6	Richmond Hill Road between Merry Mount Street and Racial Court	Weekday	AM	68.1	67.5	-0.6	71.2
			MD	65.4	64.9	-0.5	67.4
			PM	68.6	68.4	-0.2	71.3
		Saturday	MD	72.4	72.2	-0.2	75.1
			PM	71.0	70.8	-0.2	73.9
			AM	75.2	75.7	0.5	78.7
7	West Shore Expressway Southbound Service Road, South of Victory Boulevard	Weekday	MD	72.1	72.9	0.8	75.4
			PM	68.6	69.1	0.5	71.9
			MD	70.8	71.4	0.6	74.3
		Saturday	PM	69.2	70.0	0.8	72.8
			AM	71.1	68.5	-2.6	71.4
			MD	71.6	69.1	-2.5	71.1
8	Arthur Kill Road between Arden Avenue and Carlyle Green	Weekday	PM	69.1	66.6	-2.5	69.9
			MD	69.6	66.8	-2.8	69.5
			PM	70.3	67.3	-3.0	71.0
		Saturday	AM	75.0	75.0	0.0	77.4
			MD	73.9	74.1	0.2	76.8
			PM	65.3	65.4	0.1	67.7
9	Arthur Kill Road between Cortelyou and Ridgewood Avenues	Weekday	MD	70.4	70.1	-0.3	71.9
			PM	69.8	69.5	-0.3	71.7
			AM	76.3	75.8	-0.5	78.4
		Saturday	MD	74.1	73.6	-0.5	77.0
			PM	73.4	73.1	-0.3	76.5
			MD	72.0	71.7	-0.3	75.2
10	Travis Avenue between Freedom and Mulberry Avenues	Weekday	PM	72.3	72.0	-0.3	75.6
			AM	72.4	72.1	-0.3	74.7
			MD	72.6	72.2	-0.4	74.1
		Saturday	PM	73.1	72.9	-0.2	73.8
			MD	65.8	65.6	-0.2	68.5
			PM	66.8	66.6	-0.2	69.3
11	Victory Boulevard between Travis and Shenandoah Avenues	Weekday	AM	56.7	60.0	3.3	61.2
			MD	55.8	59.2	3.4	60.8
			PM	56.3	59.9	3.6	60.1
		Saturday	MD	58.3	62.3	4.0	64.1
			PM	59.7	64.3	4.6	66.2
			AM	56.7	60.0	3.3	61.2
A*	The dead end at Melvin Avenue adjacent to the proposed park	Weekday	MD	55.8	59.2	3.4	60.8
			PM	56.3	59.9	3.6	60.1
			MD	58.3	62.3	4.0	64.1
		Saturday	PM	59.7	64.3	4.6	66.2
			AM	56.7	60.0	3.3	61.2
			MD	55.8	59.2	3.4	60.8

Note: * Receptor A was selected for assessing noise from the proposed softball field.

*



- | | | |
|--|--|-------------------------------|
| Project Site Boundary | Residential | Institutional |
| Study Area Boundary (1/2-Mile Perimeter) | Residential (with Ground-Floor Retail) | Open Space |
| Noise Receptor | Commercial | Vacant Parcels |
| Industrial/DSNY Facilities | Office | Vacant Building |
| Fresh Kills Project Area | Institutional | Under Construction |
| | | Open Space Under Construction |

